


DLW-LED-039




C

D



Head C




Head D




Base



Driver Installation



C



D

Application:



Walkways



Parks and Gardens



Car parks



Prestigious




Retail



Amenity

Distribution:

INTENSITY DISTRIBUTION DIAGRAM
IN C PLANS



Features:

- Main body is made of Die casting aluminum and Extruded aluminum alloy.
- The diffuser is a clear anti-UV polycarbonate lens for high efficiency and vandal resistance.
- Lumileds 3030 led chip and Tridonic driver as regular, Sosen, Meanwell driver options.
- Easy access to LED and driver via a removable head.
- 2700-6500K color temperature options.
- Tamper proof fixings for increased vandal resistance.
- Anti-UV electrostatic powder spraying, regular color: Black, Silver, RAL7043, RAL7016
- IP65 rating water and rust proof protection.
- IK08 rating housing protection.
- Warranty is 3-5 years.

Specification:

Item No.	LED	Lumens	Wattage	CCT	CRI
DLW-LED-039C-10W	Lumileds 3030	1050LM	10W	2700-6500K	Ra≥80
DLW-LED-039C-20W	Lumileds 3030	2100LM	20W	2700-6500K	Ra≥80
DLW-LED-039C-25W	Lumileds 3030	2696LM	25W	2700-6500K	Ra≥80
DLW-LED-039D-20W	Lumileds 3030	2520LM	20W	2700-6500K	Ra≥80
DLW-LED-039D-25W	Lumileds 3030	3235LM	25W	2700-6500K	Ra≥80